

DC/DC MZM 系列

小尺寸、双路独立稳压

20-50W



物理特性

结构尺寸: 92*58*16.1mm
重量: 0.15Kg

特性

Features

- 快速动态响应 Fast dynamic response
- 功率覆盖范围广, 便于升级 Wide range of power, easy to upgrade
- 高可靠性, 长寿命设计 Design for high reliability, long lifetime
- 双路独立稳压 Two stable outputs
- 引出脚功能兼容 Pin function compatible
- 主副路电压精度高 Main & Aux output voltages with high accuracy

输入特性

Input Characteristics

电压范围: (Voltage Range)	DC-DC 12V _{DC} (Normal)	9-18V _{DC}
	24V _{DC} (Normal)	18-36V _{DC}
	48V _{DC} (Normal)	36-72V _{DC}

反压保护: 应用时外接电熔丝
(Voltage Range) (External Fuse)

输出特性

Output Characteristics

稳压精度: (Regulated Voltage Accuracy)	± 1%
电压调整率: (Line Regulation)	± 0.2%
负载调整率: (Load Regulation)	± 0.5%
温度变化率: (Temperature Coefficient)	± 0.02% /°C
电流限制点: (Output Current Limiting)	120% (Typ)
瞬态响应: (Transient Response)	400 μs

一般特性

General Characteristics

工作频率 (典型值): (Switching Frequency)	200 KHz
隔离电阻: (Isolation Resistance)	200 (Typ) MΩ
MTBF:	>500000 hrs

绝缘强度 (Insulation Voltage)

输入 - 输出: (Input-Output)	> 1500 V _{DC}
输入 - 外壳: (Input-Case)	> 1050 V _{DC}
输出 - 外壳: (Output-Case)	> 500 V _{DC}

环境特性 (Environmental Characteristics)

工作壳温: (Operation Temperature)	工业品 (Industry)	-25~+85°C
	军 I (Military I)	-40~+85°C
存储温度: (Storage Temperature)	军 II (Military II)	-55~+85°C
	工业品 (Industry)	-45~+105°C
	军品 (Military)	-55~+105°C

热阻特性

Thermal Characteristics

冷却方式: (Cooling)	热阻 (Thermal Resistance)
自然风冷: (Breeze of Nature)	4. 60°C /W
0. 5M/S	3. 30°C /W
1M/S	2. 20°C /W
1. 5M/S	1. 60°C /W
2M/S	1. 00°C /W

DC/DC MZM 系列

型号

Models

输入电压 (Vdc) Input Voltage	输入电压 (范围) Input Voltage<Range>	输出电压 (Vdc) Output Voltage	输出电流 (A) Output Current	纹波 pk-pk (mV) Ripple and noise	效率 (Typ) Efficiency	型号 Models
12	9-18	05&05	2&2	30&30	82%	MZM-X20-12D05&05
12	9-18	05&05	2&2	50&50	82%	MZM20-12D05&05
12	9-18	12&12	0.83&0.83	30&30	82%	MZM-X20-12D12&12
12	9-18	12&12	0.83&0.83	120&120	82%	MZM20-12D12&12
12	9-18	24&24	0.42&0.42	200&200	83%	MZM20-12D24&24
12	9-18	24&48	0.42&0.21	200&300	83%	MZM20-12D24&48
12	9-18	05&05	2&3	50&50	82%	MZM25-12D05&05
12	9-18	05&12	2.5&1	50&120	82%	MZM25-12D05&12
12	9-18	12&12	1&1	120&120	82%	MZM25-12D12&12
12	9-18	12&24	1&0.5	120&200	83%	MZM25-12D12&24
12	9-18	24&24	0.5&0.5	200&200	83%	MZM25-12D24&24
12	9-18	24&48	0.5&0.25	200&300	83%	MZM25-12D24&48
12	9-18	05&05	3&3	30&30	82%	MZM-X30-12D05&05
12	9-18	05&05	3&3	50&50	82%	MZM30-12D05&05
12	9-18	05&12	3&1.25	30&30	82%	MZM-X30-12D05&12
12	9-18	05&12	3&1.25	50&120	82%	MZM30-12D05&12
12	9-18	24&24	0.625&0.625	200&200	83%	MZM30-12D24&24
12	9-18	24&48	0.625&0.31	200&300	83%	MZM30-12D24&48
24	18-36	05&05	2&2	30&30	82%	MZM-X20-24D05&05
24	18-36	05&05	2&2	50&50	82%	MZM20-24D05&05
24	18-36	12&12	0.83&0.83	120&120	82%	MZM20-24D12&12
24	18-36	12&24	0.83&0.42	120&200	83%	MZM20-24D12&24
24	18-36	24&24	0.42&0.42	200&200	83%	MZM20-24D24&24
24	18-36	24&48	0.42&0.21	200&300	83%	MZM20-24D24&48
24	18-36	05&05	3&3	50&50	82%	MZM30-24D05&05
24	18-36	05&12	3&1.25	50&120	82%	MZM30-24D05&12
24	18-36	12&12	1.25&1.25	120&120	82%	MZM30-24D12&12
24	18-36	12&24	1.25&0.625	120&200	83%	MZM30-24D12&24
24	18-36	24&24	0.625&0.625	200&200	83%	MZM30-24D24&24
24	18-36	24&48	0.625&0.31	200&300	83%	MZM30-24D24&48
24	18-36	05&05	4&4	50&50	82%	MZM40-24D05&05
24	18-36	05&12	4&2.5	50&120	82%	MZM50-24D05&12
24	18-36	12&12	2&2	120&120	82%	MZM50-24D12&12
24	18-36	12&24	2&1	120&200	83%	MZM50-24D12&24
24	18-36	24&24	1&1	200&200	83%	MZM50-24D24&24
24	18-36	24&48	1&0.5	200&300	83%	MZM50-24D24&48
48	36-72	05&05	2&2	50&50	82%	MZM20-48D05&05
48	36-72	05&12	2&0.83	50&120	82%	MZM20-48D05&12
48	36-72	12&12	0.83&0.83	120&120	82%	MZM20-48D12&12
48	36-72	12&24	0.83&0.42	120&200	83%	MZM20-48D12&24
48	36-72	24&24	0.42&0.42	200&200	83%	MZM20-48D24&24
48	36-72	24&48	0.42&0.21	200&300	83%	MZM20-48D24&48
48	36-72	05&05	3&3	50&50	82%	MZM30-48D05&05
48	36-72	05&12	3&1.25	50&120	82%	MZM30-48D05&12
48	36-72	12&12	1.25&1.25	120&120	82%	MZM30-48D12&12
48	36-72	12&24	1.25&0.625	120&200	83%	MZM30-48D12&24
48	36-72	24&24	0.625&0.625	200&200	83%	MZM30-48D24&24
48	36-72	24&48	0.625&0.31	200&300	83%	MZM30-48D24&48
48	36-72	05&05	4&4	50&50	82%	MZM40-48D05&05
48	36-72	05&12	4&2.5	50&120	82%	MZM50-48D05&12
48	36-72	12&12	2&2	120&120	82%	MZM50-48D12&12
48	36-72	12&24	2&1	120&200	83%	MZM50-48D12&24
48	36-72	24&24	1&1	200&200	83%	MZM50-48D24&24

双
路

注：以上选型，型号中功率前面带“X”的为低纹波电源，纹波小于等于 30mV。Above selection, Model selection of the mark with an "X" is low ripple power supply, the ripple is less than 30mV.

■ 说明：仅列出典型型号，其它型号请确定功率、输入电压及输出电压后，致电我公司。

Only typical models and listed. If you need other models, please confirm the power, input voltage and output voltage, then phone us.